

ProCut CNC PLASMA



STANDARD

3 Axis Automatic Cutting Head
Hypertherm Edge Connect CNC
Hypertherm Plasma Power Source
19,5" Touch Screen
Hypertherm Pronest Nesting software
True Hole Technology
Torch Collision Protection System
Automatic Torch Height Control
Axis positioning accuracy $\pm 0,02$ mm
Axis positioning speed max. 20 m/min.
Remote assistance
Laser pointer for plate alignment
Automatic dust and fume extraction system
Pause / resume last part (Eg. electricity cut)

OPTIONS

Plasma Power Sources

HPRXD Series

HPR400XD

HPR800XD

XPR Series

XPR170 - choice of CORE / VVVI / OPTIMIX Automatic Gas consoles

XPR300 - choice of CORE / VVVI / OPTIMIX Automatic Gas consoles

Oxy Cutting System with capacitive sensor system

Oxy Cutting System with Auto Gas Console

Tube Cutting

Downdraft Fume Filtration System

Lateral downdraft for slag collection system

Model	Table Width (mm)	Table Length (mm)	Weight (Kg)	Z Axis (mm)	Length (mm)	Height (mm)	Width (mm)	Table Height (mm)	X Axis (mm)	Y Axis (mm)
LPL-20/40	2150	4200	800	2150	4200	170	3500	5500	2100	5400
LPL-20/60	2150	6300	800	2150	6300	170	3500	7700	2100	7000
LPL-20/80	2150	8400	800	2150	8400	170	3500	9500	2100	8600
LPL-20/120	2150	12600	800	2150	12600	170	3500	13500	2100	11800
LPL-30/40	3150	4200	800	3150	4200	170	4500	5500	2100	6600
LPL-30/60	3150	6300	800	3150	6300	170	4500	7700	2100	8700
LPL-30/120	3150	12600	800	3150	12600	170	4500	14000	2100	15200
LPL-30/240	3150	25200	800	3150	25200	170	5500	27000	2100	27600
LPL-40/60	4150	6300	800	4150	6300	170	5500	7700	2100	10800
LPL-40/120	4150	12600	800	4150	12600	170	5500	14000	2100	19800
LPL-40/150	4150	15750	800	4150	15750	170	5500	17300	2100	25700
LPL-40/240	4150	25200	800	4150	25200	170	5500	27000	2100	37800